

Pile Cutters for use with Bonded Type 1 Cut-off (Type 41) or Diamond Wheels

56PC Series



56PCK;6000;841

66PC Series



66PCK;4000;1441

Wheel Size	Operating Speed	Lever Style	MODEL NUMBER	Wheel Size	Operating Speed	Lever Style	MODEL NUMBER
8 Inch X 5/8 ID (200 mm)	6000 RPM	Standard Lever	56PCL;6000;841	10 Inch X 5/8 ID (250 mm)	6000 RPM	Standard Lever	66PCL;6000;1041
		Safety Lever	56PCK;6000;841			Safety Lever	66PCK;6000;1041
				12 Inch X 1.0 ID (300 mm)	5000 RPM	Standard Lever	66PCL;5000;1241
						Safety Lever	66PCK;5000;1241
				14 Inch X 1.0 ID (350 mm)	4000 RPM	Standard Lever	66PCL;4000;1441
						Safety Lever	66PCK;4000;1441



HP 3.0 H.P. (2.3 kW)	cfm 25 cfm (18.8 L/s) Free Speed 60 cfm (28.3 L/s) Max
Lbs 11.3 Lbs. (5.1 Kg)	SUPPLY 1/2" NPT Inlet 1/2" (13 mm) Hose Size



HP 4.0 H.P. (3.0 kW)	cfm 25 cfm (18.8 L/s) Free Speed 75 cfm (35.4 L/s) Max
Lbs 15.8 Lbs. (7.2 Kg)	SUPPLY 1/2" NPT Inlet 1/2" (13 mm) Hose Size

STANDARD EQUIPMENT

- Tool
- Operating Instructions and Service Manual
- Wrenches (sizes based on options)

ALTERNATE OPTIONS

Handles



WHEEL MOUNTING

