

Vertical Sanders for use with Surface Conditioning Abrasives

520V Series



520VK;8000;7SP

56S Series



56SK;6000;7SP

Wheel Size	Operating Speed	Lever Style	MODEL NUMBER	Wheel Size	Operating Speed	Lever Style	MODEL NUMBER
7 Inch (180 mm)	6000 RPM	Standard Lever	520VL;6000;7SP	7 Inch (180 mm)	6000 RPM	Standard Lever	56SL;6000;7SP
		Safety Lever	520VK;6000;7SP			Safety Lever	56SK;6000;7SP
	8000 RPM	Standard Lever	520VL;8000;7SP		8000 RPM	Standard Lever	56SL;8000;7SP
		Safety Lever	520VK;8000;7SP			Safety Lever	56SK;8000;7SP
				9 Inch (230 mm)	6000 RPM	Standard Lever	56SL;6000;9SP
						Safety Lever	56SK;6000;9SP



2.0 H.P.
(1.5 kW)



20 cfm (9.4 L/s) Free Speed
40 cfm (18.9 L/s) Max



6.8 Lbs.
(3.1 Kg)



1/2" NPT Inlet
1/2" (13 mm) Hose Size



3.0 H.P.
(2.3 kW)



25 cfm (18.8 L/s) Free Speed
60 cfm (28.3 L/s) Max



8.8 Lbs.
(4.0 Kg)



1/2" NPT Inlet
1/2" (13 mm) Hose Size

STANDARD EQUIPMENT

- Tool
- Operating Instructions and Service Manual
- Wrenches (sizes based on options)

ALTERNATE OPTIONS

Handles



Thumb Switch Safety Lever Standard Lever

ABRASIVE MOUNTING



Sanding Disc